

# **WORKSKIFF®**

*Aluminum Boats for Severe Service*

## **V BARGE SERIES 25' - 30'**



With its large flat deck and modified V hull design, our **V BARGE SERIES** is engineered to balance heavy load operations with speed and maneuverability. From ship docking operations to environmental clean-up work, the **V BARGE SERIES** can be used for a variety of purposes where a large flat deck is required. The Workskiff **V BARGE SERIES** can be outfitted with a center or side console, T-Top console, cabin, or a recessed cockpit for maneuverability in low clearance areas.

- **RUGGED**
- **SELF-BAILING**
- **FOAM FLOTATION**
- **TRAILER-ABLE**

- Modified "V" hull*
- Marine-grade 5086 aluminum*
- All welded construction*
- Double-welded, watertight foam-filled hull*
- CRES 316 stainless fasteners*
- Self bailing deck*
- Non-skid flooring*
- Aluminum under-deck fuel tank*
- Heavy-duty welded-on cleats*
- 12V DC electrical system*
- Hydraulic steering*
- Transducer plate*
- Zinc anode(s)*
- Multiple console and house configurations available*
- Custom options available*

**1-800-745-1727**  
**workskiff.com**

***Delivering Durability Since 1989.***

Workskiff engineers and constructs the market's toughest, most dependable industrial-grade aluminum utility boats. All of our premium models are rugged, low maintenance, and can be customized to meet your needs. See more online.

## V BARGE SERIES 25' - 30'

| Length                  | 25'         | 26'         | 27'         | 28'         | 29'         | 30'         |
|-------------------------|-------------|-------------|-------------|-------------|-------------|-------------|
| Beam                    | 8' 6"       | 8' 6"       | 8' 6"       | 8' 6"       | 8' 6"       | 8' 6"       |
| Midship Depth           | 40"         | 40"         | 40"         | 40"         | 40"         | 40"         |
| Midship Freeboard       | 27"         | 27"         | 27"         | 27"         | 27"         | 27"         |
| Draft                   | 13"         | 13"         | 13"         | 13"         | 13"         | 13"         |
| Deadrise Angle          | 12°         | 12°         | 12°         | 12°         | 12°         | 12°         |
| Fuel Capacity (gallons) | 100         | 100         | 100         | 100         | 100         | 100         |
| Cleats - 10"            | 6           | 6           | 6           | 6           | 6           | 6           |
| Weight Capacity         | 2,000 lbs   | 2,200 lbs   | 2,400 lbs   | 2,600 lbs   | 2,800 lbs   | 3,000 lbs   |
| Maximum HP              | 300         | 300         | 350         | 350         | 400         | 400         |
| Engine Capacity         | Single/Twin | Single/Twin | Single/Twin | Single/Twin | Single/Twin | Single/Twin |



|                      | Thickness | Aluminum |
|----------------------|-----------|----------|
| Bottom               | 0.250"    | #5086    |
| Sides                | 0.190"    | #5086    |
| Transom              | 0.250"    | #5086    |
| Deck                 | 0.190"    | #5052    |
| Seat Boxes / Lockers | 0.190"    | #5052    |
| Cabin                | 0.190"    | #5052    |

### Applications:

- > HOMELAND SECURITY
- > ENVIRONMENTAL RESEARCH
- > OIL SPILL RESPONSE
- > SURVEY & CONSTRUCTION
- > DIVING OPERATIONS

info@workskiff.com  
Phn 360-707-1727  
Fax 360-757-0892

Call for a Full Consultation.

Let our experienced sales team walk you through our complete line of extreme watercraft. We'll help you find the right solution for your field.